

DEWALT®

PORTABLE RADIANT HEATERS



EGI CONFIDENTIAL Not To Be Shared



DXRH008E

PORTABLE RADIANT

This 1.17 - 2.4 kW radiant heater connects directly to a 0.45 kg cylinder and is the perfect solution for heating enclosed spaces like large tents up to 21m².

SPECIFICATIONS:

Radiant Gas Heater	1.17 - 2.4 kW
Heating Area	21 m ²
Minimum Tank Size	0.45 kg
Run Time	5 hrs
Oxygen Detection Sensor	Yes
Gas Cartridges	Threaded
Ignition Type	Piezo
Tip-Over Safety Shut-Off	Yes
Warranty	2 Year Limited





DXRH012E

PORTABLE RADIANT

This 2.8 - 3.07 kW radiant heater connects directly to (2) 0.45 kg cartridges or (1) 18.14 kg tank. Features (3) USB ports used to charge portable electronics & accessories, integrated high speed fan to quickly circulate heat and has a powerful LED light bar.

SPECIFICATIONS:

Radiant Gas Heater	2.8 - 3.07 kW
Heating Area	27 m ²
Minimum Tank Size	0.45 kg
Run Time	7 hrs (2 Cartridges)
Oxygen Detection Sensor	Yes
Gas Cartridges	Threaded
Ignition Type	Electric
Tip-Over Safety Shut-Off	Yes
Warranty	2 Year Limited





DEWALT®

FORCED AIR PROPANE HEATERS



EGI CONFIDENTIAL *Not To Be Shared*



DXPH060E

FORCED AIR PROPANE

This 17.5 kW forced air propane heater connects directly to a 9 kg tank. Features a rugged glove friendly handle, heavy duty steel construction, high temperature limit switch and high output fan.

SPECIFICATIONS:

Radiant Gas Heater	17.5 kW
Heating Area	116 m ²
Tank Size	9 kg
Run Time	7 hrs high / 14 hrs low
Net Weight	9.5 kg
Variable Output	No
Ignition Type	Piezo
Cubic Meter Per Hour	510 m ³ /h
Warranty	2 Year Limited





DXPH125E

FORCED AIR PROPANE

This 22 - 37 kW forced air propane heater connects directly to a 18.14 kg tank. Features a rugged glove friendly handle, heavy duty steel construction, high temperature limit switch and high output fan.

SPECIFICATIONS:

Radiant Gas Heater	22-37 kW
Heating Area	290 m ²
Minimum Tank Size	18.14 kg
Run Time	7 hrs high / 11.5 hrs low
Net Weight	10.4 kg
Variable Output	Yes
Ignition Type	Piezo
Cubic Meter Per Hour	510 m ³ /h
Warranty	2 Year Limited





DEWALT®

FORCED AIR DIESEL HEATERS



DXKH080E

FORCED AIR DIESEL

This 23.5 kW forced air diesel heater features multi-fuel capability (diesel #1, diesel #2, kerosene, JP8, #1 fuel oil, #2 fuel oil), cold weather start (-17° C), overheat shut-off, fuel gauge and thermostat.

SPECIFICATIONS:

Radiant Gas Heater	23.5 kW
Heating Area	186 m ²
Tank Size	23 L
Run Time	9.6 hrs
Net Weight	14 kg
On Board Diagnostics	No
Ignition Type	Electric
Thermostat	Yes
Warranty	2 Year Limited





DXKH125E

FORCED AIR DIESEL

This 37 kW forced air diesel heater features multi-fuel capability (diesel #1, diesel #2, kerosene, JP8, #1 fuel oil, #2 fuel oil), cold weather start (-17° C), overheat shut-off, fuel gauge and thermostat.



SPECIFICATIONS:

Radiant Gas Heater	37 kW
Heating Area	290 m ²
Tank Size	37.8 L
Run Time	10.8 hrs
Net Weight	23.5 kg
On Board Diagnostics	Yes
Ignition Type	Electric
Thermostat	Yes
Warranty	2 Year Limited



DXKH180E

FORCED AIR DIESEL

This 53 kW forced air diesel heater features multi-fuel capability (diesel #1, diesel #2, kerosene, JP8, #1 fuel oil, #2 fuel oil), cold weather start (-17° C), overheat shut-off, fuel gauge and thermostat.



SPECIFICATIONS:

Radiant Gas Heater	53 kW
Heating Area	418 m ²
Tank Size	57 L
Run Time	11.25 hrs
Net Weight	29 kg
On Board Diagnostics	Yes
Ignition Type	Electric
Thermostat	Yes
Warranty	2 Year Limited



DEWALT®

INDUSTRIAL ELECTRIC HEATERS



IN DEVELOPMENT

INDUSTRIAL ELECTRIC

Developing a line of durable industrial electric heaters for Europe based on North American proven heaters.

Model#	DXH165	DXH330	DXH1000TS	DXH2000TS	DXH2003TS
Stock #	F340635	F340640	F340645	F340650	F340655
UPC	856795406356	856795406400	856795406455	856795406509	856795406554
Kilowatts	1.5 kW	3.3 kW	10 kW-Hi 7 kW-Lo	20 kW-Hi 13 kW-Lo	20 kW-Hi 13 kW-Lo
Multiple Heat Setting	NO	NO	YES	YES	YES
BTU/HR	5,118	11,260	34,121-(Hi) 23,884-(Lo)	68,242-(Hi) 44,357-(Lo)	68,242-(Hi) 44,357-(Lo)
CFM Output	135	230	394	661	661
Volt	115V	240V	240V	240V	240V
Minimum Breaker	13.5 Amp	2 pole 15 amp	2 pole 50 Amp-(Hi) 30 Amp -(lo)	2 pole 100 Amp-(Hi) 60 Amp -(lo)	2 pole 100 Amp-(Hi) 60 Amp -(lo)
Phase	Single	Single	Single	Single	3 Phase
Fan Only Operation	NO	NO	NO	YES	YES
Cord/Plug Included	YES	NO	NO	NO	NO
Weight	14 lbs.	19 lbs.	35 lbs.	45 lbs.	48 lbs.
Shipping Ctn Size (In Inches)	14 x 11 x 14	15.75 x 13.5 x 17	25 x 14.5 x 18.5	29.5 x 16.5 x 21. 25	29.5 x 16.5 x 21. 25

European Product Sizes In Development:

- 3.3 k on low end 240 plug - (F/G/J)
- 5.0 kw middle end 240 plug - (F/G/J)
- 7 kw-10kw high end commercial plug - (F/G/J)

US Specification Chart



DXH165-36-lowes16.jpg



DXH165-Controls.jpg



DXH165-Front-Fan.jpg



DXH165-Handle.jpg



DXH2003TS-On-Cart.jpg

